



100% Cotton	100% Polyester	Poly/Cotton Blends	Nylon	Lycra®/Spandex	Leather	Sublimated Polyester	Home Iron Compatible	CPSIA Certified	Temperature (EasyPress® users add approximate 30°)	Pressure	Time (Seconds)	Peel Carrier
-------------	----------------	--------------------	-------	----------------	---------	----------------------	----------------------	-----------------	--	----------	----------------	--------------

Siser® Heat Transfer Vinyl Reference

EasyWeed®	✓	✓	✓			✓		✓	✓	305° F / 150° C	medium	10-15	hot or cold
EasyWeed® EcoStretch™	✓	✓	✓		✓	✓		✓	✓	250° F / 121° C	medium	10-15	hot
EasyWeed® Electric	✓	✓	✓			✓		✓	✓	305° F / 150° C	medium	15	hot or cold
EasyWeed® Extra		✓	✓			✓		✓	✓	305° F / 150° C	light / medium	10-15	hot or cold
EasyWeed® Sub Block		✓					✓		✓	265° F / 130° C	medium / firm	15	warm
EasyWeed® Adhesive	✓	✓	✓					✓	✓	275° F / 135° C	medium	5-10	hot
EasyReflective®	✓	✓	✓	✓				✓	✓	305° F / 150° C	medium	15	warm
Easy® Puff	✓	✓	✓		✓			✓		280° F / 138° C	firm	8-10	hot
Easy® Glow	✓	✓	✓					✓		305° F / 150° C	medium	15	cold or warm
Aurora™	✓	✓	✓					✓		305° F / 150° C	medium	15	cold
BlackBoard®	✓	✓	✓					✓	✓	275° F / 135° C	medium	15	warm
Brick® 600	✓	✓	✓					✓	✓	310° F / 155° C	medium / firm	15-20	cold
Glitter	✓	✓	✓			✓		✓	✓	320° F / 160° C	medium	15-20	warm
Holographic	✓	✓	✓			✓		✓	✓	320° F / 160° C	medium	10-15	cold
Metal	✓	✓	✓					✓		305° F / 150° C	medium	10-15	cold
Sparkle™	✓	✓	✓					✓	✓	305° F / 150° C	medium	15	hot or cold
StripFlock® Pro	✓	✓	✓			✓		✓	✓	310° F / 155° C	medium	15	warm
Twinkle™	✓	✓	✓					✓	✓	305° F / 150° C	medium / firm	15	warm
EasySubli®	✓	✓	✓					✓	✓	310° F / 155° C	medium	15	warm
EasyColor™ DTV™	✓	✓	✓					✓	✓	310° F / 155° C	medium	15	warm
EasyPatterns® Plus	✓	✓	✓			✓		✓	✓	305° F / 150° C	medium	10-15	hot or cold

CPSIA certified means that the material has been independently tested and is free of lead and phthalates and is safe for application on children's products. Please test for compatibility on your garment before committing to production.



Ceramic	Drywall	Glass	Metal	Plastic	Wood	Surface Characteristics	Thickness	Durability	Cutting Blade Recommendation
---------	---------	-------	-------	---------	------	-------------------------	-----------	------------	------------------------------

Siser® EasyPSV® Reference

EasyPSV® Starling™	✓		✓	✓	✓	✓	matte / gloss	3 mils / 76.2 microns	3-6 year	45°
EasyPSV® Glitter	✓		✓	✓	✓	✓	smooth gloss	3 mils / 76.2 microns	5 year	45°
EasyPSV® Etch	✓		✓	✓	✓	✓	matte	3 mils / 76.2 microns	5-7 year	45°
EasyPSV® Glow	✓		✓	✓	✓	✓	gloss	4.2 mils / 107 microns	indoor usage only	45°
EasyPSV® Brushed	✓		✓	✓	✓	✓	gloss	6.9 mils / 175 microns	indoor / outdoor	45°
EasyPSV® BlackBoard®	✓	✓	✓	✓	✓	✓	matte	5 mils / 127 microns	1 year clean removability	45°
EasyPSV® Holographic	✓	✓	✓	✓	✓	✓	pearlescent	3.15 mils / 80 microns	3 year clean removability	45°
EasyPSV® Patterns	✓		✓	✓	✓	✓	patterned	3.94 mils / 100 microns	3 year	45°

Please test for compatibility on your surface before committing to decoration. Not recommended for use with dishwasher (except for *Starling*) or microwave.