EASYPSV® APPLICATION INSTRUCTIONS

1. Place EasyPSV® with the liner side down and cut your design. (DO NOT reverse/mirror your design)
2. Weed excess vinyl.
3. Remove the application tape's paper liner. Place tape on top of *EasyPSV* and burnish with a squeegee.
4. Lift the application tape with *EasyPSV* attached away from the paper liner to expose the sticky adhesive.
5. Place the application tape on your desired object and burnish with a squeegee to fully adhere the design.
6. Gently peel away the application tape, leaving just your *EasyPSV* design on the object.

EasyPSV® Starling™ by Avery Dennison®

Specifications: Smooth gloss and matte finish · 3 mils/76.2 mircons · 45° blade

Outdoor Durability	Up to 5 years depending on climate and UV exposure.
Adhesive	Permanent Clear Acrylic
Liner	78# Bleached Kraft
Minimum, Application Temperature	+50° F
Shelf Life	2 years when stored at 70° F and 50% relative humidity

Not recommended for use with microwave or painted drywall.

EasyPSV® Permanent - Glitter

Specifications: Smooth gloss finish · 3 mils/76.2 microns · 45° blade

Outdoor Durability	Up to 5 years depending on climate and UV exposure.
Adhesive	Permanent, Solvent Based
Liner	78# Kraft
Minimum, Application Temperature	+40° F
Shelf Life	2 years when stored at 70° F and 50% relative humidity.

Not recommended for use with dishwasher, microwave, or painted drywall.

EasyPSV® BlackBoard, Etch, Holographic)

Specifications: Matte finish · 3 mils/76.2 mions · 45° blade

Outdoor Durability	Up to 3 years depending on usage and exposure to elements
Adhesive	Removable, Water Based
Liner	78# Kraft
Minimum, Application Temperature	+40° F
Shelf Life	1 year when stored at 70° F and 50% relative humidity.

Not recommended for use with dishwasher or microwave.

Recommended Accessories: Vinyl Cutter, Siser® EZ Weeder®, EasyPSV® Application Tape, Siser® Squeegee

12-2021